

NILFISK VHS210 C2D2

Next-level power,  
filtration, and safety



**NILFISK**

# May the power be with you – and safety too

Meet the Nilfisk VHS210 C2D2. Taking industrial vacuums to the next level with unseen power. Expect no less than an immaculate machine offering ultimate single-phase performance in C2D2 environments with our most powerful brushless motor, the highest filtration, and an extensive range of antistatic accessories.

Not only is this machine explosion-proof. It's bullet-proof. It has all the 3rd-party approvals and certifications for maximum combustible dust cleaning in Class II, Division 2 (C2D2) classified zones. It's fully grounded, easy to use, and highly maneuverable due to its modest footprint. Simply making it suited for cleaning wherever high-level

hygiene is required, and performance, safety, and filtration are crucial. The Nilfisk VHS210 C2D2 is an explosion proof singlephase industrial vacuum suitable for use in C2D2 environments and is highly recommended for the food, manufacturing, and pharma industries.



**The powerful, brushless single-phase motor** is capable of 10,000 or more hours of maintenance-free service life.

**All models are 3rd-party certified**, providing unique safety for the operator by meeting the highest safety standards on the market.

**The steel container with a filling capacity of over 13 gallons** is fitted with a practical drop-down release system.

## Top features and benefits include:

- Maintenance-free single-phase motor with up to 150 cfm and 92" of water lift
- Gravity unload system with plastic bag or Longopac (endless bag)
- Increased filter cleaning efficiency of the innovative PullClean system due to a high-pressure difference
- Highest safety standards on the market, all vacuums are 3rd party certified
- Highest filtration performance
- Ideal for overhead cleaning to avoid contamination
- Explosion-proof and fully bonded and grounded



**PULLCLEAN™**



### Technical specifications

Description	Unit	VHS210N1 L C2D2
Rated power	kW	1.45
Frequency	Hz	60
Insulation class		I
Protection class	IP	65
Voltage	V	120
Current draw, rated	(A)	17.5
Airflow with 3 m. hose	cfm	150
Max waterlift	in H <sub>2</sub> O	92
Sound pressure level	dB(A)	67
Dimensions LxWxH	in	34x24x61
Weight	lb	163
Inlet	mm	70
Main filter type		M-Class Start filter
Main filter area	ft <sup>2</sup>	19
Container capacity	l	50

Nilfisk, Inc.  
 9435 Winnetka Avenue North  
 Brooklyn Park, MN 55445  
 Phone 800-850-5559 • Fax 800-989-6566  
[www.nilfisk.us](http://www.nilfisk.us)

Nilfisk Canada Co.  
 240 Superior Boulevard  
 Mississauga, Ontario, Canada L5T 2L2  
 Phone 800-668-8400 • Fax 800-263-5111  
[www.nilfisk.ca](http://www.nilfisk.ca)

# NILFISK